


1490nm FP Laser Diode SM Module

Features

- Center wavelength 1490nm
- Low threshold current
- High speed $t_r/t_f < 0.7\text{ns}$
- Built-in InGaAs monitor detector
- Four-lead package
- Wide operating temperature -20°C to 85°C
- Hermetically sealed TO-18 package in pigtailed or receptacle housing with FC, ST or SC connector



Applications

- Fiber In The Loop
- ATM, SONET/SDH
- Motorway and railway networks
- Intra and interoffice links
- Subscriber loops
- Trunk supervision
- Test instruments

Specifications

Optical And Electrical Characteristics (T=25+/-3°C unless specified otherwise)


Parameter	Symbol	Test Conditions	Min	Typical	Max	Units
Center Wavelength	λ	25°C	1480	1490	1500	nm
Spectral Width	$\Delta\lambda$	$P_0=5\text{mw(RMS)}$	-	1.6	2.5	nm
Threshold Current	I_{th}	25°C -40 to 85°C		12 24	18 35	mA
Operating Voltage	V_{op}	P_0	-	1.1	1.6	V
Rise/Fall Time	t_r / t_f	10-90%	-		0.2	ns
Optical Output Power	P_0	$I_{th}+30\text{mA}$				
-1			0.1	0.25	-	mW
-2			0.4	0.55	-	mW
-3			0.7	0.9	-	mW
-4			1.2	-	-	mW
Monitor Current (PD)	I_m	$P_0, V_{RD}=1\text{V}$	15		75	mW
Dark Current (PD)	I_d	$V_{RD}=5\text{V}$	-	-	200	nA
Return Loss (w/isolator)		$T_0=0\sim+60^\circ\text{C}$	40	-	-	dB
Tracking Error	E_t	-40 to 85°C		± 1.0		dB

1490nm FP Laser Diode SM Module

Absolute Maximum Ratings (T=25 °C)

Parameter	Symbol	Min.	Max.	Unit
Forward Current (LD)	I_{op}	-	120	mA
Reverse Bias (LD)	V_{RL}	-	2	V
Reverse Bias (PD)	V_{RD}	-	10	V
Operating Case Temperature	T_c	-20	+85	°C
Storage Temperature	T_{stg}	-40	+100	°C


Ordering Information



1490nm FP Laser Diode SM Module


Pin Connections

BOTTOM VIEW




UNIT : MM

C TYPE
PIN CONNECTIONS




D TYPE
PIN CONNECTIONS



Dimension



Pigtail Type





1490nm FP Laser Diode SM Module

Receptacle Type



FC-PM





FC-BM





ST-BM



ST-PM




SC



1490nm FP Laser Diode SM Module

Sugar Cube

Dimension (ST Receptacle) Unit mm



Pin Connections (Type A)

PIN No.	FUNCTION
1	NC
2	ANODE
3	CATHODE
4	NC
5	NC
6	ANODE or NC
7	ANODE or NC
8	NC

Pin Connections (Type B)

PIN No.	FUNCTION
1	NC
2	NC
3	LD Cathode (LD-)
4	NC
5	NC
6	LD Anode (LD+), PD-
7	Monitor PD Anode (PD+)
8	NC

1490nm FP Laser Diode SM Module

1490 nm FP LD
Fiber-coupled Power vs. Drive Current

